



| | | |
|----------------------------------|----------------------------------------|--|
| Type no. | EFB 690 17 | |
| Article no. | 012690170101 | |
| Standards | DIN EN 50342-1, 50342-4 | |
| Application | Starter battery | |
| Electrical data | | |
| Rated voltage | 12V | |
| Rated capacity | 190 Ah (K20) | |
| Cold start current | 1050 A (EN) | |
| Dimensions and weights | | |
| Box | B | |
| Length max. | 513mm | |
| Width max. | 223mm | |
| Box height max. | 195mm | |
| Total height max. | 220mm | |
| Battery weight | Ca. 46,0 kg (+/- 5 %) | |
| Electrolyte density | Approx. 1,28 kg/l | |
| Electrolyte | Diluted sulphuric acid | |
| Items/pallet | 21 | |
| Pallet ID | Euro pallet | |
| Items per layer | 7 | |
| Features | | |
| Base hold-down | B00 | |
| Layout | 3 | |
| Terminal | 1 | |
| Separator | PE bag separator with glass mat | |
| Degassing | Battery with central degassing | |
| Flame arrester | Integrated | |
| Performance identification | W4 - C2 - >V3 - E3 | |
| Maintenance ¹⁾ | | |
| Water consumption | W4 | |
| Refill water | Distilled or demineralised (DIN 43530) | |
| Self-discharge | Approx. 3 % per month | |
| Charging current | Approx. 1/10 of the rated capacity | |
| Charging voltage ²⁾ | max. 14,8 V | |



¹⁾ All the listed values relate to room temperature +25° C
²⁾ Recommendation with an external, voltage-regulated charge.
 Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.original